

## High performance – great results!

features	SUPERFORST	MAXIFORST
mulches wood up to	40 cm [16"] Ø	60 cm [24"] Ø
working speed	0-5 km/h	0-5 km/h
ISO 3-point rear linkage	cat. 3 central articulated	cat. 3 & 4 central fixed
gearbox with freewheel	1000 rpm	1000 rpm
shaft input	1 3/4" Z=20	2 1/4" Z=22
alignment system	EVA™	ADAM™
belt drive	double	double
number belts	10	12
hood	hydr. adjustable	hydr. adjustable
skids	S	adjustable in height
front and rear protection	triple/single chains	triple/single chains
standard rotor	swinging hammers	fixed knives

SUPERFORST and MAXIFORST are the "high performers" for felling trees, and clearing the ground after the wood harvest or after catastrophes etc.

The best partners for professionals!

**EVA™ system:**  
hydraulic tilting of the mulcher with PTO shaft alignment for faster working, better results and longer lifetime of the PTO shaft.

**centrifugal clutch**  
for slow start and protection of the PTO shaft  
(SUPERFORST option  
MAXIFORST standard)

**swinging hammer**  
(SUPERFORST standard)

**rakes** on the hood or on the guard frame for an easier handling of the material to be mulched (option)

SUPERFORST

SUPERFORST								
working width cm ["]	total width cm ["]	depth cm ["]	height cm ["]	weight* kg [lb]	swinging hammers #	OPT 228: MINI DUO #	kW min-max	HP min-max
200 [79]	244 [96]	140 [55]	125 [49]	3.800 [8,400]	41	42	172-260	230-350
225 [89]	269 [106]	140 [55]	125 [49]	4.100 [9,000]	47	48	172-260	230-350
250 [98]	294 [116]	140 [55]	125 [49]	4.400 [9,700]	52	54	172-260	230-350

\* The weight of the machine is approximate, it refers to the standard version without any options and it may vary.

\*\* The indicated kW and HP refer to the power required at the PTO output shaft, not to the nominal tractor power.

